

# DATASHEET

## 2 SKYLINE 2.0



### GENERAL

Art.Nr: SL-501

E-class number: 40-02-01-90

Standards: ABZ,CEN/TS 16415:  
2013,EN 795:2012/C,  
UNI 11578:2015

Net weight: 0.00 kg

Gross weight: 0.00 kg

# DATASHEET

## 2 SKYLINE 2.0

The SKYLINE 2.0 horizontal lifeline system secures up to three people simultaneously over long distances in areas where there is a risk of falling. Whether work needs to be carried out on the floor, on the ceiling or on the wall - thanks to its design, the SKYLINE 2.0 can be used flexibly in areas where there is a risk of falling. It is mainly used on large flat roofs, in production facilities, for maritime applications, at sewage treatment plants and silos or in logistics. It does not matter whether the substructure is made of wood, concrete or steel. The SKYLINE 2.0 system has a building authority approval (abZ) Z-14.9-869 from the German Institute for Building Technology and is also tested and certified in accordance with EN 795:2012 TYPE C, CEN/TS 16415:2013 and UNI 11578:2015.

### FEATURES

|                            |                        |
|----------------------------|------------------------|
| Colour:                    | Silver                 |
| Type mounting base:        | Steel                  |
| Mounting type:             | Machine screws         |
| Thickness mounting base:   | 8 mm                   |
| Horizontal systems:        | Horizontal rope system |
| Maximum number of persons: | 3                      |
| Minimum temperature:       | -30 °C                 |
| Maximum temperature:       | 80 °C                  |
| Rope access technique:     | No                     |

### DIMENSIONS

|                 |          |
|-----------------|----------|
| Rope length:    | 200.00 m |
| Max height:     | 8 mm     |
| Minimum height: | 8 mm     |

### MATERIAL

|           |                 |
|-----------|-----------------|
| Material: | Stainless Steel |
|-----------|-----------------|